





Telic Picotrack Accessories

Product	Picture	Short Summary	Part Number	Picotrack Power
USB-A _ Micro USB-B Cable		For use with cigarette lighter charger or to charge with laptop; Cable length: 1 m	17005	●
USB Power Supply		USB power adapter without connection cable for Telic's telematics products	17003	●
Picotrack Cigarette Lighter Charger		Without USB Cable; Requires micro USB-A cable (Part Number 17005)	17004	●
Picotrack Car Installation Cable		Cable with open wires and Micro-USB connector; Voltage range 9 - 32 Volt; Cable length: 1 m	17000	●
Picotrack Case		IP69K Enclosure for Picotrack Power	17014	●
Magnetic Plate for Picotrack Case		Magnetic Plates for Picotrack Case	17015	●
Config-Tool Cable for Picotrack		Device specific cable for configuration of Picotrack / Picotrack Power devices	16207	●





Telic Picotrack Endurance Accessories

Product	Picture	Short Summary	Part Number	Picotrack Endurance Rechargeable	Picotrack Endurance Primary	Picotrack Endurance Solar
USB-A _ Micro USB-B Cable		For use with cigarette lighter charger or to charge with laptop; Cable length: 1 m	17005	●		
USB Power Supply		USB power adapter without connection cable for Telic's telematics products	17003	●		
Picotrack Cigarette Lighter Charger		Without USB Cable; Requires micro USB-A cable (Part Number 17005)	17004	●		
Endurance Primary Cell		Replacement 12,6 Ah primary cell for Picotrack Endurance Primary	16020		●	
Charging cable for Endurance Rechargeable		Charging cable for Picotrack Endurance Rechargeable; Cable length: 2 m	17013	●		
Charging cable for Endurance Solar		Charging cable for Picotrack Endurance Solar; Cable length: 2 m	17031			●
Config-Tool Cable for Picotrack Rechargeable		Device specific cable for configuration of Picotrack Endurance Rechargeable	16211	●		
Config-Tool Cable for Picotrack Primary+Solar		Device specific cable for configuration of Picotrack Endurance Primary or Solar	16210		●	●

Telic SBC Accessories

Product	Picture	Short Summary	Part Number	SBC3 CAN Products	SBC-AVL	SBC-AVL Power
SBC3 Connection Cable (7-wires)		2 of these cables for SBC3-CAN version Cable length: 1 m	16300	●		
SBC-AVL Cigarette Lighter Charger		Specifically designed for SBC-AVL; Cable length: 1,35 m	17024		●	●
SBC-AVL Connection Cable		Open wire device-specific connection cable; 10 wires; Cable length: 1 m	16301		●	●
OBD II Power Supply Cable		2-pin OBD-II connector cable for power supply only; Cable length: 1 m	17023		●	●
OBD II CAN Cable		4-pin OBD-II connector/cable for power supply + CAN High/Low; Cable length: 1 m	17027		●	
RS232 Level Shifter		Level shifter from LV-TTL (3.3V) to RS232 (12V); Open Wires (VCC; GND; RS232 Rx &Tx; TTL Rx & Tx); Cable length: 1 m	16105			●
1-wire Temperature Sensor		1-wire Temperature sensor; Cable length: 7 m; Temperature range: -55 °C to +125 °C; Accuracy: ± 0,5°C (in range -10 °C to +85 °C)	90029	●	●	●
Config-Tool Cable for SBC3 CAN		Device specific cable for configuration of the SBC3 CAN (including the variants SBC3 CAN Power and SBC3 CAN EXT); Sub-D 9-pin Connector	16214	●		

Telic Antenna Accessories

Product	Picture	Short Summary	Part Number
Rectangular Antenna		FME female connector	12016
Stub Antenna		FME female connector	12019
Roof antenna		To screw on top of a roof; Cable length: 2 m	12012
Combo Antenna		Glue antenna cable to fix to window / dashboard inside a vehicle; Cable length: 3 m	16004

Note: These antennas are suitable for SB3 CAN Variant "SBC3 CAN EXT" with external antenna connector.